

COMMERCIAL

VULCAN LED CORROSION PROOF – 4FT AND 2FT

VULCAN LED Corrosion Proof
Available in: 1200mm (4ft) Single & Double
600mm (2ft) Single & Double



- LED replacement for 18W or 36W fluorescent fittings
- 100 lumens per circuit watt
- 5,000K cool white light output
- 50,000 hour average lamp life
- IP65, can be used for internal or external applications
- Options available through Conversions: Emergency, 0-10V Dimmable, Microwave Sensor and 110V applications
- Complete with stainless steel clips
- Plastic clips available RCPPCLIPS



	1.2M 1 x 24W	1.2M 2 x 24W	0.6M 1 x 12W	0.6M 2 x 12W
	R124LEDCP-01	R224LEDCP-01	R112LEDCP-01	R212LEDCP-01
Comparable to:	1x36W T8 Fluorescent	2x36W T8 Fluorescent	1x18W T8 Fluorescent	2x18W T8 Fluorescent
Total Power (W):	24	48	12	24
Power Factor:	>0.9	>0.9	>0.9	>0.9
Total Light Output (lm):	2,700	4,800	1,300	2,650
Beam Angle (deg):	110	110	110	110
Lux at 1m (lux):	685	1,350	360	720
CCT L100 (K):	5,000	5,000	5,000	5,000
CRI at L100:	70	70	72	72
Efficacy (lm/cctW):	108	105	108	110
Lifetime L70 F10 (hrs):	50,000	50,000	50,000	50,000
Length (mm):	1,258	1,258	660	660
Width (mm):	93	140	93	140
Height (mm):	97	97	97	97
Box Qty:	1	1	1	1
Weight (kg):	2.5	3.0	1.1	1.35
IP:	65	65	65	65

